


LINEAR ADJUSTABLE SERIES  
LED TRACK SPOT LIGHT



IP20 | CE | CB | | |


Body: Die-cast aluminium  
Housing: Die-cast aluminium  
Optic: PC Diffuser  
Weight: 0.84kg  
CTN: 18PCS



White  
 Black  
 Silver

ORDERING CODE	Power (W)	Beam Angle (°)	CCT (K)	Hot Lumen (Lm)	LOR (%)	UGR	On/Off	DRIVER 1-10V	DALI	Triac
<b>HLA1200-W/B/S-830</b>			3000	1560						
<b>HLA1200-W/B/S-840</b>	30	110	4000	1623	40%	<19	✓	✓	✓	✓
<b>HLA1200-W/B/S-850</b>			5000	1686						

2835 3000K




LINEAR ADJUSTABLE SERIES  
LED TRACK SPOT LIGHT



IP20 | CE | CB | | |

Body: Die-cast aluminium  
Housing: Die-cast aluminium  
Optic: PC Diffuser  
Weight: 0.84kg  
CTN: 12PCS



White  
 Black  
 Silver

ORDERING CODE	Power (W)	Beam Angle (°)	CCT (K)	Hot Lumen (Lm)	LOR (%)	UGR	On/Off	DRIVER 1-10V	DALI	Triac
<b>HLA1800-W/B/S-830</b>			3000	1994						
<b>HLA1800-W/B/S-840</b>	36	110	4000	2033	40%	<19	✓	✓	✓	✓
<b>HLA1800-W/B/S-850</b>			5000	2102						

2835 3000K

