




OCTOPUS High-Bay fitting with Super compact design with the greatest efficient passive cooling system. The high presser ADC12 Alloy one piece Aluminum casting body give super strong durability and positions that offers the greatest performance of heat dissipation. OCTOPUS has an various accessories that made it passable for all kind of application of use in commercial and industrial. The LED's Long life and energy efficiency offer significant advantages in terms of running costs.




IP65 | CE | CB |

Body: Die-cast aluminium
Housing: Die-cast aluminium
Optic: High efficiency PMMA
Weight: 9kg
CTN: 2PCS




White Black Silver

ORDERING CODE	Power (W)	Beam Angle (°)	CCT (K)	Hot Lumen (Lm)	LOR (%)	UGR	On/Off	DRIVER 1-10V	DALI	Triac
ODP4200-W/B/S-830			3000	10050						
ODP4200-W/B/S-840	200	77	4000	11530	80%	<19	✓	✓	✓	✓
ODP4200-W/B/S-850			5000	13584						




CREE CXA2540

3000K




IP65 | CE | CB |

Body: Die-cast aluminium
Housing: Die-cast aluminium
Optic: High efficiency PMMA
Weight: 10kg
CTN: 1PCS



White Black Silver

ORDERING CODE	Power (W)	Beam Angle (°)	CCT (K)	Hot Lumen (Lm)	LOR (%)	UGR	On/Off	DRIVER 1-10V	DALI	Triac
ODP4100-W/B/S-830			3000	10050						
ODP4100-W/B/S-840	200	77	4000	11530	80%	<19	✓	✓	✓	✓
ODP4100-W/B/S-850			5000	13584						



CREE CXA2540

3000K

